

Auto Switching



Connecting the Scanner

Connect USB cable to the USB port of a host PC.



USB Device Type

HID Keyboard*



CDC (SPP)



Factory Default



Display F/W Version



Auto Sense

Enable Auto Sensing *



Disable Auto Sensing (Trigger Mode)



Encoding

Remark: For displaying Traditional Chinese character on your Windows PC, please scan the QR code below to look for corresponding product name and download **Windows registry setting utility for Traditional Chinese input**.

UTF-8*



Big 5



Good Read

Good Read Beep Enable*



Good Read Beep Disable



* : Default Option

Thank you for purchasing the unitech product.

For other product documentation, please scan the QR code for more information.



HID Keyboard Character Delay

1 ms*



5 ms



10 ms



20 ms



50 ms



100 ms



HID Keyboard Block Delay

10 ms*



50 ms



100 ms



500 ms



1 Sec.



3 Sec.



HID Keyboard Case

Auto Trace*



To Lower



To Upper



HID Keyboard Language

US English*



UK English



Swiss



Swedish



French



ALT Mode



Danish



Spanish



Norwegian



Italian



Partial ALT



German



Japanese



* : Default Option

Thank you for purchasing the unitech product.

For other product documentation, please scan the QR code for more information.

